

# shindaiwa®

## welder-generators

6 The Dell, Enterprise Drive,  
Four Ashes, Wolverhampton  
England, WV10 7DF  
Phone: +44 (0) 1902 791855  
Email: info@shindaiwa.co.uk

### The best combination of a welder-generator in the world today!

## WELDERS OF DISTINCTION

### SHINDAIWA 165UK



ECO Mode  
Welding Range 40-165A  
Electrode Size – 2.0-4.0 mm  
1 Phase output 2.5kVA 110V  
Digital Display  
Powered by Subaru Petrol engine  
Auto-Idling  
Fuel Tank Capacity – 12 Ltrs  
Quiet Technology

**Low Noise Levels: -90 dB LWA**  
Dimensions (mm): L704, W494, H625  
Weight: 78Kg  
Optional Extras:  
Paralleling Box  
2 Wheel Trolley  
Welding Cables  
Accessories

### SHINDAIWA 200UK



ECO Mode  
Welding Range 50-200A  
Electrode Size – 2.0-5.0 mm  
1 Phase output 3kVA 110V-CTE  
Digital Display  
Kubota Z482 Diesel Engine  
Auto-Idling  
Fuel Tank Capacity – 15 Ltrs  
Quiet Technology

**Low Noise Levels: -94 dB LWA**  
Dimensions (mm): L998, W603, H773  
Weight: 220Kg  
Optional Extras:  
2 Wheel Road Trailer  
Paralleling Box  
2 Wheel Trolley  
Welding Cables  
Accessories

### SHINDAIWA 300UK



ECO Mode  
Welding Range 35-300A  
Electrode Size – 2.0-6.0 mm  
1 Phase output 3kVA 110V-CTE  
3 Phase = 8kVA 415V  
Digital Display  
Kubota D722 Diesel Engine  
Auto-Idling  
Fuel Tank Capacity – 37 Ltrs

Quiet Technology  
**Low Noise Levels: -88 dB LWA**  
Dimensions (mm): L1410, W566, H760  
Weight: 350Kg  
Optional Extras:  
Remote Control, Chalwyn Valve, Spark  
Arrestor Silencer, Paralleling Box  
2 Wheel Road Trailer  
Welding Cables  
Accessories

### SHINDAIWA 500UK



ECO Mode/Auto-Idling  
Double Operator  
CC/CV Welding Modes  
1 Phase output 4.0kVA 110V-CTE  
3 Phase – 18kVA 415V  
Digital Display  
Kubota V1505 Diesel Engine  
Fuel Tank Capacity – 63 Ltrs  
Quiet Technology  
Mode switch for welding, generating  
or both.  
EMC Approved

CC Welding Range: 60-500A/1 op,  
or 30-280A two operators  
CC Electrode Size: Welding 2-8mm,  
Gouging 10mm  
CV Voltage Range: 14-40v/1 op,  
or 14-29v/2 operators  
CV Wire size: 0.6-2.4mm/1 op,  
or 0.6-2.0mm/2 operators  
**Low Noise Levels: -94 dB LWA**  
Dimensions (mm) Base mounted: L1680, W700,  
H950, Weight: 630Kg  
Optional Extras:  
As per Eco 300UK Model